

```

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity:65.0%
Test Distance:8.000m [K=0.7063]
Remarks: LED:HL-A-2835D68W-2-S1-08L-HR3
          (0.2W超高光效), PCB:LS-M-10S9P
          -V1.0, 电源: SC42W300-1050CG-4
          (1050mA)

```

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	3250	3245	3249	3268	3288	3296	3294	3278	0- 10	316.9	316.9	7.88,7.88
20	2920	2908	2917	2966	3014	3019	3005	2971	10- 20	885.5	1202	29.9,29.9
30	2051	2022	2051	2182	2309	2314	2267	2178	20- 30	1206	2408	59.9,59.9
40	1007	840.8	815.0	1040	1255	1140	978.4	958.9	30- 40	977.7	3386	84.2,84.2
50	164.0	148.3	157.5	215.1	263.3	224.0	172.1	158.8	40- 50	391.7	3778	94,94
60	29.79	27.55	30.11	41.88	52.02	46.46	37.60	32.96	50- 60	84.66	3862	96.1,96.1
70	3.247	4.271	5.198	5.944	6.712	8.186	8.867	6.921	60- 70	13.21	3875	96.4,96.4
80	2.645	3.605	4.395	4.884	5.383	6.620	7.238	5.657	70- 80	5.755	3881	96.6,96.6
90	3.565	3.682	4.159	5.233	6.373	7.310	7.558	6.137	80- 90	5.802	3887	96.7,96.7
100	6.103	6.040	6.425	7.608	8.765	9.088	8.845	7.788	90-100	6.879	3894	96.9,96.9
110	10.38	10.23	10.47	11.40	12.31	12.45	12.18	11.46	100-110	9.887	3904	97.1,97.1
120	16.85	16.34	16.25	16.88	17.52	17.32	16.96	16.85	110-120	13.83	3918	97.5,97.5
130	25.73	24.29	23.56	24.03	24.60	23.87	23.28	24.09	120-130	18.21	3936	97.9,97.9
140	34.68	32.72	31.64	32.01	32.53	31.47	30.75	32.08	130-140	21.70	3957	98.5,98.5
150	42.04	40.71	39.75	39.30	39.08	38.80	38.93	40.12	140-150	22.55	3980	99,99
160	48.07	48.36	47.82	45.63	43.79	44.97	46.73	47.58	150-160	19.92	4000	99.5,99.5
170	54.29	54.49	54.01	52.18	50.63	51.49	52.89	53.68	160-170	14.04	4014	99.9,99.9
180	56.28	56.34	56.37	56.35	56.32	56.33	56.34	56.32	170-180	5.201	4019	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-27

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity:65.0%
Test Distance:8.000m [K=0.7063]
Remarks: LED:HL-A-2835D68W-2-S1-08L-HR3
(0.2W超高光效), PCB:LS-M-10S9P
-V1.0, 电源: SC42W300-1050CG-4
(1050mA)

LUMINANCE LIMITATION CURVES

Test:U:220.70V I:0.1650A P:34.100W PF:0.9350 Freq:50.00Hz Lamp Flux:4019.17x1 lm		
Name: LS-M 1200 32W CCT(3000K)	Type: 长条形	
MFR.:	DIM.: 1205*36*92mm	
	SUR.: 1192*30mm	



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	960	1490
80	435	723
75	294	507
70	271	434
65	311	477
60	1702	1720
55	3802	4205
50	7290	7000
45	18146	14971


C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-27

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: HL-A-2835D68W-2-S1-08L-HR3
(0.2W超高光效), PCB: LS-M-10S9P
-V1.0, 电源: SC42W300-1050CG-4
(1050mA)

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.70V I:0.1650A P:34.100W PF:0.9350 Freq:50.00Hz		
Lamp Flux:4019.17x1 lm		
Name: LS-M 1200 32W CCT(3000K)	Type: 长条形	
MFR.:	DIM.: 1205*36*92mm	
	SUR.: 1192*30mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.04	1.04	1.04	.99	.99	.99	.97
1.0	1.09	1.07	1.04	1.07	1.04	1.02	1.02	1.00	.98	.98	.96	.95	.94	.93	.92	.90
2.0	1.01	.96	.93	.99	.95	.92	.95	.92	.89	.92	.89	.87	.88	.86	.84	.82
3.0	.93	.88	.84	.92	.87	.83	.88	.84	.81	.86	.82	.79	.83	.80	.78	.76
4.0	.86	.80	.76	.85	.79	.75	.82	.78	.74	.80	.76	.73	.78	.74	.71	.70
5.0	.80	.74	.69	.79	.73	.69	.77	.72	.68	.75	.70	.67	.73	.69	.66	.64
6.0	.75	.68	.63	.74	.67	.63	.72	.66	.62	.70	.65	.62	.68	.64	.61	.59
7.0	.69	.63	.58	.69	.63	.58	.67	.62	.58	.66	.61	.57	.64	.60	.57	.55
8.0	.65	.59	.54	.64	.58	.54	.63	.57	.53	.61	.57	.53	.60	.56	.53	.51
9.0	.61	.55	.50	.60	.54	.50	.59	.54	.50	.58	.53	.49	.57	.52	.49	.48
10.0	.57	.51	.47	.57	.51	.47	.56	.50	.46	.54	.50	.46	.54	.49	.46	.44



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-27

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: HL-A-2835D68W-2-S1-08L-HR3
(0.2W超高光效), PCB: LS-M-10S9P
-V1.0, 电源: SC42W300-1050CG-4
(1050mA)

WEC AND CCEC

Test:U:220.70V I:0.1650A P:34.100W PF:0.9350 Freq:50.00Hz		
Lamp Flux:4019.17x1 lm		
Name: LS-M 1200 32W CCT(3000K)	Type: 长条形	
MFR.:	DIM.: 1205*36*92mm	
	SUR.: 1192*30mm	

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.192	.109	.035	.184	.105	.033	.170	.097	.031	.156	.090	.029	.144	.083	.027		
2.0	.184	.101	.031	.178	.098	.030	.165	.092	.029	.154	.086	.027	.143	.081	.026		
3.0	.176	.094	.028	.170	.091	.027	.160	.087	.026	.150	.082	.025	.140	.078	.024		
4.0	.168	.087	.026	.163	.085	.025	.153	.081	.024	.145	.078	.023	.136	.074	.023		
5.0	.160	.082	.024	.156	.080	.023	.147	.077	.023	.140	.074	.022	.132	.071	.021		
6.0	.153	.077	.022	.149	.075	.022	.141	.072	.021	.134	.070	.021	.128	.067	.020		
7.0	.146	.072	.020	.142	.071	.020	.136	.069	.020	.129	.066	.019	.123	.064	.019		
8.0	.139	.068	.019	.136	.067	.019	.130	.065	.019	.124	.063	.018	.119	.061	.018		
9.0	.133	.065	.018	.131	.064	.018	.125	.062	.018	.120	.060	.017	.115	.058	.017		
10.0	.128	.061	.017	.125	.060	.017	.120	.059	.017	.115	.057	.016	.111	.056	.016		

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.216	.216	.216	.184	.184	.184	.126	.126	.126	.072	.072	.072	.023	.023	.023	
1.0	.197	.182	.169	.169	.157	.145	.116	.108	.101	.067	.062	.058	.021	.020	.019	
2.0	.183	.158	.136	.157	.136	.118	.108	.094	.082	.062	.055	.048	.020	.018	.016	
3.0	.172	.139	.113	.147	.120	.098	.101	.083	.069	.058	.049	.041	.019	.016	.013	
4.0	.163	.125	.096	.139	.108	.083	.096	.075	.059	.055	.044	.035	.018	.014	.011	
5.0	.155	.114	.083	.133	.098	.073	.091	.069	.051	.053	.040	.030	.017	.013	.010	
6.0	.148	.105	.074	.127	.091	.064	.087	.063	.045	.051	.037	.027	.016	.012	.009	
7.0	.141	.097	.066	.122	.084	.058	.084	.059	.041	.049	.035	.024	.016	.011	.008	
8.0	.136	.091	.061	.117	.079	.053	.081	.056	.037	.047	.033	.022	.015	.011	.007	
9.0	.131	.086	.056	.113	.075	.049	.078	.053	.035	.046	.031	.021	.015	.010	.007	
10.0	.126	.082	.052	.109	.071	.046	.076	.050	.032	.044	.030	.019	.014	.010	.006	

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-27

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED:HL-A-2835D68W-2-S1-08L-HR3
 (0.2W超高光效), PCB:LS-M-10S9P
 -V1.0, 电源: SC42W300-1050CG-4
 (1050mA)

UGR(Unified Glare Rating) Table

Test:U:220.70V I:0.1650A P:34.100W PF:0.9350 Freq:50.00Hz										
Lamp Flux:4019.17x1 lm										
Name: LS-M 1200 32W CCT(3000K)					Type: 长条形					
MFR.:					DIM.: 1205*36*92mm					
					SUR.: 1192*30mm					
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	18.1	19.1	18.4	19.3	19.6	17.7	18.7	18.0	18.9	19.2
3H	17.9	18.8	18.2	19.1	19.4	17.5	18.4	17.8	18.7	19.0
4H	17.8	18.7	18.2	19.0	19.3	17.4	18.3	17.7	18.6	18.9
6H	17.7	18.5	18.1	18.8	19.2	17.3	18.1	17.7	18.4	18.7
8H	17.7	18.5	18.0	18.8	19.1	17.3	18.1	17.6	18.4	18.7
12H	17.6	18.4	18.0	18.7	19.0	17.2	18.0	17.6	18.3	18.7
4H 2H	17.8	18.7	18.2	19.0	19.3	17.4	18.3	17.8	18.6	18.9
3H	17.6	18.4	18.0	18.7	19.1	17.2	18.0	17.6	18.3	18.6
4H	17.5	18.2	17.9	18.6	18.9	17.1	17.8	17.5	18.2	18.5
6H	17.4	18.0	17.9	18.4	18.8	17.0	17.6	17.5	18.0	18.4
8H	17.4	17.9	17.8	18.3	18.8	17.0	17.5	17.4	17.9	18.4
12H	17.3	17.8	17.8	18.3	18.7	17.0	17.5	17.4	17.9	18.3
8H 4H	17.4	17.9	17.8	18.3	18.8	17.0	17.5	17.4	17.9	18.4
6H	17.3	17.7	17.8	18.2	18.7	16.9	17.3	17.4	17.8	18.3
8H	17.2	17.6	17.7	18.1	18.6	16.8	17.2	17.3	17.7	18.2
12H	17.2	17.5	17.7	18.0	18.6	16.8	17.1	17.3	17.6	18.2
12H 4H	17.3	17.8	17.8	18.3	18.7	16.9	17.4	17.4	17.9	18.3
6H	17.2	17.6	17.7	18.1	18.6	16.8	17.2	17.3	17.7	18.2
8H	17.2	17.5	17.7	18.0	18.6	16.8	17.1	17.3	17.6	18.2
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 3.2 / -11.2					+ 2.9 / - 9.7				
1.5H	+ 5.2 / - 8.1					+ 4.9 / - 7.0				
2.0H	+ 7.0 / -12.1					+ 6.2 / -10.0				

CIE Pub.117, 4019 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 4.8$)
Area: 0.035 m²

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-27

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity:65.0%
Test Distance:8.000m [K=0.7063]
Remarks: LED:HL-A-2835D68W-2-S1-08L-HR3
(0.2W超高光效), PCB:LS-M-10S9P
-V1.0, 电源: SC42W300-1050CG-4
(1050mA)

UTILIZATION FACTORS TABLE

Test:U:220.70V I:0.1650A P:34.100W PF:0.9350 Freq:50.00Hz Lamp Flux:4019.17x1 lm		
Name: LS-M 1200 32W CCT(3000K)	Type: 长条形	
MFR.:	DIM.: 1205*36*92mm	
	SUR.: 1192*30mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	82	74	70	81	74	70	80	74	70	66
0.80	90	83	79	89	83	79	87	82	78	74
1.00	95	89	85	94	88	84	92	88	84	79
1.25	100	94	90	98	93	89	96	92	88	83
1.50	103	97	94	101	97	93	99	95	92	86
2.00	106	101	98	104	100	97	101	98	95	89
2.50	108	104	100	106	102	99	102	99	97	90
3.00	110	106	103	108	104	102	104	101	99	92
4.00	112	109	106	110	107	105	105	103	101	93
5.00	113	111	109	111	109	107	106	105	103	94
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-27

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED:HL-A-2835D68W-2-S1-08L-HR3
 (0.2W超高光效), PCB:LS-M-10S9P
 -V1.0, 电源: SC42W300-1050CG-4
 (1050mA)

ISOCANDELA DIAGRAM

Test:U:220.70V I:0.1650A P:34.100W PF:0.9350 Freq:50.00Hz Lamp Flux:4019.17x1 lm		
Name: LS-M 1200 32W CCT(3000K)	Type: 长条形	
MFR.:	DIM.: 1205*36*92mm	
	SUR.: 1192*30mm	




C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-09-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity:65.0%
Test Distance:8.000m [K=0.7063]
Remarks: LED:HL-A-2835D68W-2-S1-08L-HR3
(0.2W超高光效), PCB:LS-M-10S9P
-V1.0, 电源: SC42W300-1050CG-4
(1050mA)

AAI Figure

Test:U:220.70V I:0.1650A P:34.100W PF:0.9350 Freq:50.00Hz Lamp Flux:4019.17x1 lm		
Name: LS-M 1200 32W CCT(3000K)	Type: 长条形	
MFR.:	DIM.: 1205*36*92mm	
	SUR.: 1192*30mm	

Flux out:2856 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: HL-A-2835D68W-2-S1-08L-HR3
(0.2W超高光效), PCB: LS-M-10S9P
-V1.0, 电源: SC42W300-1050CG-4
(1050mA)

ISOLUX DIAGRAM


Test:U:220.70V I:0.1650A P:34.100W PF:0.9350 Freq:50.00Hz Lamp Flux:4019.17x1 lm		
Name: LS-M 1200 32W CCT(3000K)	Type: 长条形	
MFR.:	DIM.: 1205*36*92mm	
	SUR.: 1192*30mm	



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: HL-A-2835D68W-2-S1-08L-HR3
(0.2W超高光效), PCB: LS-M-10S9P
-V1.0, 电源: SC42W300-1050CG-4
(1050mA)

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-27

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: HL-A-2835D68W-2-S1-08L-HR3
(0.2W超高光效), PCB: LS-M-10S9P
-V1.0, 电源: SC42W300-1050CG-4
(1050mA)

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.70V I:0.1650A P:34.100W PF:0.9350 Freq:50.00Hz Lamp Flux:4019.17x1 lm		
Name: LS-M 1200 32W CCT(3000K)	Type: 长条形	
MFR.:	DIM.: 1205*36*92mm	
	SUR.: 1192*30mm	

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	30	60	90	120	150	180	210	240	270	300	330						
0	3369	3365	3363	3362	3364	3367	3369	3367	3364	3362	3363	3365						
5	3334	3329	3327	3329	3336	3344	3352	3355	3356	3355	3351	3343						
10	3250	3246	3245	3249	3261	3275	3288	3295	3297	3294	3285	3271						
15	3117	3110	3110	3118	3138	3160	3180	3189	3190	3184	3169	3147						
20	2920	2908	2907	2917	2948	2983	3014	3021	3018	3005	2985	2957						
25	2605	2564	2551	2564	2629	2702	2766	2767	2748	2715	2685	2648						
30	2051	2022	2022	2051	2136	2229	2309	2322	2306	2267	2214	2142						
35	1541	1449	1407	1415	1518	1637	1741	1729	1685	1628	1596	1567						
40	1007	873	809	815	958	1122	1255	1192	1087	978	954	964						
45	449	381	355	371	473	583	668	609	521	431	409	415						
50	164	149	147	157	196	235	263	241	207	172	160	157						
55	76.3	78.3	81.0	84.4	90.1	95.4	99.3	98.4	95.6	91.3	87.1	82.1						
60	29.8	27.5	27.6	30.1	37.9	45.9	52.0	49.1	43.8	37.6	34.3	31.7						
65	4.60	5.25	6.07	7.06	8.46	9.86	11.1	12.0	12.4	12.1	10.5	8.02						
70	3.25	3.95	4.60	5.20	5.70	6.19	6.71	7.77	8.60	8.87	7.86	5.98						
75	2.66	3.41	4.06	4.60	4.92	5.22	5.57	6.56	7.37	7.70	6.82	5.14						
80	2.64	3.31	3.90	4.40	4.73	5.04	5.38	6.27	6.97	7.24	6.42	4.89						
85	2.93	3.51	4.05	4.55	4.96	5.36	5.76	6.54	7.13	7.28	6.49	5.03						
90	3.56	3.58	3.78	4.16	4.85	5.62	6.37	7.09	7.53	7.56	6.80	5.47						
95	4.66	4.55	4.66	4.99	5.76	6.59	7.34	7.72	7.83	7.62	6.99	6.01						
100	6.10	5.99	6.09	6.42	7.19	8.02	8.77	9.07	9.10	8.85	8.24	7.33						
105	8.00	7.87	7.95	8.25	8.97	9.74	10.4	10.7	10.6	10.4	9.84	9.05						
110	10.4	10.2	10.2	10.5	11.1	11.7	12.3	12.5	12.4	12.2	11.8	11.2						
115	13.3	13.1	13.0	13.2	13.7	14.3	14.8	14.8	14.6	14.4	14.1	13.7						
120	16.8	16.4	16.2	16.2	16.6	17.1	17.5	17.4	17.2	17.0	16.9	16.8						
125	21.0	20.3	19.9	19.7	20.1	20.5	20.8	20.6	20.2	20.0	20.1	20.4						
130	25.7	24.6	23.9	23.6	23.8	24.2	24.6	24.1	23.6	23.3	23.7	24.5						
135	30.4	29.0	28.0	27.5	27.7	28.2	28.5	27.9	27.2	26.9	27.5	28.6						
140	34.7	33.2	32.2	31.6	31.8	32.2	32.5	31.8	31.1	30.8	31.4	32.7						
145	38.7	37.3	36.2	35.6	35.7	35.9	36.1	35.5	35.0	34.8	35.5	36.8						
150	42.0	41.1	40.3	39.7	39.4	39.2	39.1	38.8	38.8	38.9	39.6	40.6						
155	45.0	44.8	44.5	44.0	43.0	42.1	41.4	41.6	42.2	43.0	43.6	44.3						
160	48.1	48.4	48.3	47.8	46.4	44.9	43.8	44.4	45.5	46.7	47.4	47.8						
165	51.3	51.8	51.8	51.3	49.7	48.0	46.8	47.5	48.7	50.1	50.7	51.1						
170	54.3	54.5	54.4	54.0	52.8	51.6	50.6	51.1	51.9	52.9	53.5	53.9						
175	56.2	56.3	56.2	55.9	55.2	54.5	54.0	54.1	54.5	55.0	55.4	55.8						
180	56.3	56.3	56.4	56.4	56.4	56.3	56.3	56.3	56.3	56.3	56.3	56.3						

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-09-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: HL-A-2835D68W-2-S1-08L-HR3
(0.2W超高光效), PCB: LS-M-10S9P
-V1.0, 电源: SC42W300-1050CG-4
(1050mA)